



LEICA TEMPUS ASPH.

Technical data



Red-dot sight	Leica Tempus ASPH. 3.5 MOA	Leica Tempus ASPH. 2.0 MOA
Order No.	55 500	55 502
Scope of delivery	protection cover, optics cleaning cloth, opener for battery holder, allen key for adjusting the height and lateral adjustment screw, 2 mounting bolts	protection cover, optics cleaning cloth, opener for battery holder, allen key for adjusting the height and lateral adjustment screw, 2 mounting bolts
Lens element:		
Magnification	1.0 x	1.0 x
Front lens dimensions (W x H)	21 x 25 mm	21 x 25 mm
Height adjustment	100 MOA	100 MOA
Side adjustmenst	100 MOA	100 MOA
Adjustments per click	1.1 MOA	1.1 MOA
Parallax free	43.7 yds / 40 m	43.7 yds / 40 m
Aspheric lens	yes	yes
Dot:		
Red-dot intensity levels	12	12
Dot size (subtensions)	3.5 MOA (10 cm/100 m)	2.0 MOA (5,8 cm/100 m)
Color red peak	645 nm / dominant 630 nm	645 nm / dominant 630 nm
Temperature		
Operational	-13 up to +122 °F / -25 up to +50 °C	-13 up to +122 °F / -25 up to +50 °C
Storage	-31 up to +158 °F / -35 up to +70 °C	-31 up to +158 °F / -35 up to +70 °C
Plus/minus push buttons (functions)	any button = ON hold for 3 sec = OFF AUTO-OFF at 4 hours without operation 12 intensity settings	any button = ON hold for 3 sec = OFF AUTO-OFF at 4 hours without operation 12 intensity settings
Battery	1 x 3 V CR2032 Lithium-type	1 x 3 V CR2032 Lithium-type
Operating time	approx. 250 h	approx. 250 h
Waterproof	yes, 3 ft. / 1 m depth (0.1 bar)	yes, 3 ft. / 1 m depth (0.1 bar)
Housing	aluminum	aluminum
Shooting stability	28.2 oz / 800 g (1 millisecond)	28.2 oz / 800 g (1 millisecond)
Dimensions (L x H x D)	2.1 x 1.35 x 1.1 in / 53.5 x 34.5 x 28 mm	2.1 x 1.35 x 1.1 in / 53.5 x 34.5 x 28 mm
Weight	1.41 oz / 40 g (incl. battery)	1.41 oz / 40 g (incl. battery)